



US010665243B1

(12) **United States Patent**  
**Whitmire et al.**

(10) **Patent No.:** **US 10,665,243 B1**  
(45) **Date of Patent:** **May 26, 2020**

(54) **SUBVOCALIZED SPEECH RECOGNITION**

(56) **References Cited**

(71) Applicant: **Facebook Technologies, LLC**, Menlo Park, CA (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Eric Michael Whitmire**, Redmond, WA (US); **Laura Cristina Trutoiu**, Seattle, WA (US)

5,937,384 A \* 8/1999 Huang ..... G06K 9/6297  
704/251  
6,487,531 B1 \* 11/2002 Tosaya ..... G10L 15/20  
704/223  
7,181,391 B1 \* 2/2007 Jia ..... G10L 15/18  
704/231  
8,364,486 B2 \* 1/2013 Basir ..... G10L 15/02  
704/254  
9,564,128 B2 \* 2/2017 Park ..... G10L 15/24  
9,977,496 B2 \* 5/2018 Maltz ..... G06F 3/013  
9,984,683 B2 \* 5/2018 Li ..... G10L 15/16  
2006/0074656 A1 \* 4/2006 Mathias ..... G10L 15/063  
704/243  
2007/0106501 A1 \* 5/2007 Morita ..... G06F 3/015  
704/200  
2008/0288022 A1 \* 11/2008 Van der Borgh ..... H04R 25/43  
607/57  
2009/0010456 A1 \* 1/2009 Goldstein ..... H04R 25/02  
381/110

(73) Assignee: **Facebook Technologies, LLC**, Menlo Park, CA (US)

(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 235 days.

(21) Appl. No.: **15/791,295**

(22) Filed: **Oct. 23, 2017**

**Related U.S. Application Data**

(60) Provisional application No. 62/420,834, filed on Nov. 11, 2016.

(Continued)

*Primary Examiner* — Fariba Sirjani

(74) *Attorney, Agent, or Firm* — Fenwick & West LLP

(51) **Int. Cl.**

**G10L 15/25** (2013.01)

**G06F 3/16** (2006.01)

**G10L 15/32** (2013.01)

**G10L 15/187** (2013.01)

**G10L 15/14** (2006.01)

**ABSTRACT**

A system for subvocalized speech recognition includes a plurality of sensors, a controller and a processor. The sensors are coupled to a near-eye display (NED) and configured to capture non-audible and subvocalized commands provided by a user wearing the NED. The controller interfaced with the plurality of sensors is configured to combine data acquired by each of the plurality of sensors. The processor coupled to the controller is configured to extract one or more features from the combined data, compare the one or more extracted features with a pre-determined set of commands, and determine a command of the user based on the comparison.

(52) **U.S. Cl.**

CPC ..... **G10L 15/25** (2013.01); **G06F 3/167** (2013.01); **G10L 15/142** (2013.01); **G10L 15/187** (2013.01); **G10L 15/32** (2013.01)

(58) **Field of Classification Search**

CPC ..... G10L 15/25; G10L 15/142; G10L 15/187; G10L 15/32; G06F 3/167

See application file for complete search history.

**18 Claims, 4 Drawing Sheets**

